

Santon Aqua-Dri Hand Dryers



Santon Aqua-dri hand driers are economical and efficient to run, being fully automatic and operating only when hands are placed below the unit for drying.

Compact in size, Aqua-dri requires little wall space for installation, and avoids the issues associated with other forms of hand drying such as the need for continual replenishment of clean materials and subsequent disposal of waste.

Features:

- Energy efficient - automatic 'Touch-Free' (proximity sensor) operation with auto switch-off.
- Slimline design - only 110mm deep, suitable for confined areas.
- Small footprint - requires only small amount of wall space.
- Electrical connection - unit attaches to pre-fitted & wired wall plate for ease of installation.
- Concealed connections - electrical supply made from rear of unit for neater, tidier installation.

Specification:

Approvals:

Complies with the requirement of EN60335-2-23 and European Community Directives (CE)

Capacities:

Air Volume 15 ltr/s.

Air Velocity 16 m/s.

Controls:

Automatic 'Touch Free' (proximity sensor) operation with auto switch-off.

Factory Safety:

Fully automatic ON/OFF switching.

Self re-setting thermal cut-out.

Thermal fuse.

IP rating 23.

Guarantee:

Two years product guarantee, from date of purchase, with on-site service support. Full details are contained in the Installation Instructions supplied with each unit.

Motor Fan:

Air Volume 15 ltr/s.

Air Velocity 16 m/s.

Relative drying time 35s.

Cont...

Outer Casing:

Impact resistant ABS plastic.

Rating:

6.4A/1500W @ 240V single phase AC

6.1A/1400W @ 230V single phase AC

Safety Features:

Fully automatic ON/OFF switching.

Self re-setting thermal cut-out.

Thermal fuse.

IP rating 23.

Installation Details:**Electrical:**

The installation must comply with BS 7671 'Requirements for Electrical Installations' (IEE Wiring regulations). It must be permanently connected to the electrical supply through a 13A double pole linked isolating switch with a minimum contact separation of 3mm in each pole. Where the drier is fitted in a room containing a fixed bath or shower the drier must be installed to comply with BS7671 regulation 601-02-01 Classification Zones, which details the safe distance away from a bath or shower basin which the drier can be fitted. Minimum cable size - 1.5mm

Fixing:

Mounting plate is secured to wall by four fixing screws, and electrical connections are made.

Drier unit is then attached and secured with fixing screw.

Guarantee:

Two years product guarantee, from date of purchase, with on-site service support. Full details are contained in the Installation Instructions supplied with each unit.

Deal electrical Supplies

Tel; 01304-239240

Fax: 01304-239204

Email: info@dealec.co.uk

www.dealec.co.uk